

Base Tubular Cleaning Unit

The Base Tubular Cleaning Unit provides inside and outside diameter cleaning for an array of tubular sizes and types at an affordable price. The unit has a durable design, user friendly controls, minimized maintenance and is manufactured with the highest quality.

Standard Features

- Single wire brush assembly for tubular outside diameter, Qty 7, 2" Wide 10" diameter wire brushes.
- Pneumatic brush assembly floating system to handle dimensional variations.
- Inside diameter cleaning via a rigid pipe to accommodate rattling motor or high-pressure water attachment with a soft impact support system to reduce the possibility of tubular thread damage during conveying.
- Cyclonic dust and debris collection system, Dust and debris-laden air is forced into a steel tapered cone creating a high-velocity cyclone separating particles into the debris cabinet. Fine dust is then exhausted out of the building.
- 40 HP electric-powered hydraulic system to efficiently perform all pipe handling operations.
- Left or Right tubular loading setup.
- Conveyors with 6' wheel spacing to feed tubular goods to cleaning system at adjustable feed rates.
- Operator and maintenance-friendly mechanical control pedestal positioned up to 10' away for maximum safety.

Building & Service Requirements

Electrical:

- 230V 3ph 60 HZ 150 Amps OR 480V 3ph 60 HZ 100 Amps
- Others by Request

Pneumatic:

in

- 110 psi @ 175 cfm (ID Rattling)
- 110 psi @ 45 cfm (Non-ID Rattling)
- Work area as per layout drawing 10900.116
- Customer responsible for all service terminations & building modifications
- Signed installation agreement, if applicable





Optional Features

- Enclosures to reduce sound levels below 85db and contain dust and debris.
- Dust and debris collection system with filtered exhaust. Dust is forced across cartridge-style filter elements virtually eliminating any airborne particles.
- Baghouse filtration system.
- Outside diameter extreme scale and rust removal system.
- Range 3 tubular capacity.
- Small tubing capacity.
- Water blasting accessory package to accept up to 10,000 psi water blasting system.

Contact us today to learn more.

855-655-5406 | sales@rr-mfg.com | rr-mfg.com